



The Singapore LNG Terminal located on Jurong Island is Singapore's only liquefied natural gas terminal.

The LNG terminal receives and stores LNG vaporisers that raise its temperature and unloaded from LNG carriers. The supercooled turn it back into gaseous form. The used, it must first pass through seawater

LNG is kept in special storage tanks until it is regasified natural gas is then sent through a shifts monitor the terminal's operations needed by power plants. But before it can be network of pipes to power plants. The LNG terminal itself is located on a 40ha plot of

secured Jurong Island. Staff on 12-hour round the clock from a control room.

How the LNG terminal works Natural gas is liquefied and transported by tankers from overseas and regasified for distribution and sale. 1. LNG is pumped from carriers and stored in LNG storage tanks. 2. Boil-off gas, generated from the vaporised LNG in the tanks, is

3. Seawater open rack vaporisers regasify LNG. 4. The gas is then sent through the pipeline network to power stations.

recondensed and recovered as LNG.

Natural gas and LNG


noticeable.

 Natural gas is odourless, colourless, non-corrosive and non-toxic. Tetrahydrothiophene, or THT, which has a strong pungent smell, is added to

natural gas to make gas leaks more


 LNG is less than half the weight of water.

 LNG is flammable only if the amount of gas is 5 per cent to 15 per cent in air. LNG is used mostly for electricity generation.




SLNG premises, which can collectively hold 800.000 cubic m of LNG. Each tank is large enough to fit two Airbus A-380 aircraft, stacked on top of each other. Its inner layer is made of special combination of 9 per cent nickel

steel, while the outer shell is concrete, with insulation materials in between the two layers, allowing them to withstand the sub-zero temperatures of the LNG. Multiple safety devices and sensors monitor the conditions within each tank.



Tank is large enough to fit two Airbus A-380 aircraft.

LNG carrier Natural gas is liquefied, reducing its volume by 600 times and making it cost-efficient to transport over long distances. It is loaded into ships and brought to Singapore from various overseas locations, including Australia. The process of berthing and LNG is liquefied at minus 161 deg C unloading the LNG takes around 24 hours. and transported in insulated tanks.



Keppel Merlimau Cogen, one of seven power plants in Singapore, has the ability to transmit 1,300MW of electricity into Singapore's power grid.

Seven power plants in Singapore generate most of the island's electricity for mass consumption. Most of these plants use what is known as combined cycle gas turbine technology to produce power.

This technology allows power plants to maximise input energy, harnessing heat that is produced from an initial energy generation process to create steam, which is used to generate even more electricity.

How technology in a power station works

1 A mixture of fuel and air enters the gas turbine. Combustion occurs, which powers the turbine and generates electricity.

2 Heat generated goes into the heat recovery steam generator, turning demineralised water into steam, which then travels to the steam turbine.

3 The blades of the steam turbine turn, generating electricity.

Vatura

Gas

200 years

50 years

Transformer

4 Residual steam goes into the condenser, which turns it into demineralised water and is pumped back to the heat recovery steam generator.

6 Electricity travels to a transformer.

6 The transformer steps up the voltage and sends the electricity to the grid.



SP Group's distribution control centre where monitoring of the power grid and remote switching is done.

The entire energy process is jointly managed by the EMA's Power System that overall demand is met. In the event of a power disruption, the PSCC distribution control centre.

The PSCC uses sophisticated systems restored quickly. to monitor the pressure and flow of natural gas and to control power generation plants' output to ensure

Control Centre (PSCC) and SP Group's coordinates responses by various stakeholders to ensure power is

The PSCC monitors the system until electricity is stepped down from 66kV, after which SP Group will take over.



The underground transmission cable tunnel network comprises three tunnels: North-South Tunnel, East-West Tunnel and Jurong Island-Pioneer Tunnel.

35-55m Deep tunnel sewerage system

of underground tunnels, serving as the 'highway' of the

3m Sewage and current power grids

12m Underpass

8-25m Underground expressways

30m MRT tunnels

electricity network.

60-80m Underground transmission cable tunnels

BY THE NUMBERS

-161 deg C Temperature at which LNG is liquefied

>1,000 deg C Temperature in the gas turbine

400kV

Highest voltage in the transmission network



Number of robots (above) that patrol the underground transmission

Estimated number of substations in Singapore

Some estimate that the world's natural gas reserves can last 200 years, compared with around 50 years for oil. Sources: SLNG, KMC, EMA, SP GROUP ST PHOTOS: KEVIN LIM, KELVIN CHNG, ONG WEE JIN STRAITS TIMES GRAPHICS: LEE HUP KHENG

Heat recovery

steam generator